

93S Hoses



Tel: +44 (0) 1274 550500
Fax: +44 (0) 1274 550501
Email: sales@aerovac.com
Website: www.aerovac.com

- Stainless steel, braided, PTFE lined autoclave hose.
- Fitted with an internal spring to prevent collapse of the PTFE liner.
- External end protection springs prevent excessive bending of the hose.
- Supplied with a silicone outer sheath, which protects the stainless steel braiding from damage and allows the hose to be placed directly on the vacuum bag, without fear of puncture from exposed braiding.

SPECIFICATION

- Maximum operating temperature 200°C +
- Maximum working pressure 2500psi
- Maximum length 12m
- Diameter (internal) 10mm (including sleeve)
- Diameter (external) 20mm
- Hoses are made to the exact length required. Termination threads ¼" BSP (male) are standard. Also available are 90° elbow fittings and other adaptors to suit alternative thread sizes. 90° elbows and non return couplings are fitted on request.

STORAGE & HANDLING

- No special requirements.
- Handling of these products must conform to individual company guidelines and health and safety regulations.

Aerovac Systems Ltd www.aerovac.com	Aerovac Systems Italy S.r.l www.aerovac.it	Aerovac Systèmes France www.aerovac.fr	Richmond Aircraft Products www.richmondaircraft.com
---	---	---	--

Aerovac Systems Ltd.

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith. All values stated are nominal. For further details about tolerances please contact Aerovac Systems quality department.

Revised: February 2010