

# F400

## Porous Polyester Peel Ply Fabric

- F400 is a porous, heavy weight, polyester Peel Ply
- Scoured and heat set, to remove any impurities collected during the spinning and weaving processes
- Not coated with any release solutions and as such will not contaminate the composite part
- No necessity to clean the surface before painting or subsequent bonding operation
- Particularly recommended for use on high temperature (180°C+), high pressure autoclave cures, where stripability of lighter weight, untreated nylons and polyesters can be difficult and time consuming
- Recommended for use with phenolic resins

### PHYSICAL PROPERTIES

- |                            |                      |
|----------------------------|----------------------|
| • Maximum Cure Temperature | 210°C                |
| • Treatment                | Heat set and scoured |
| • Fabric Weight            | 115g/m <sup>2</sup>  |
| • Colour                   | White                |

### AVAILABILITY & PACKAGING

- |                         |                   |
|-------------------------|-------------------|
| • Roll size             | 100m x 1.52m wide |
| • Slit widths available |                   |

### STORAGE & HANDLING

- No special storage conditions required

## Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: [sales@aerovac.com](mailto:sales@aerovac.com) website: [www.aerovac.com](http://www.aerovac.com)

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.