

FF03/05/06/10AP

Self Adhesive PTFE Coated Glass Fabric Tool Release Sheet

- PTFE coated glass fabric tool release sheet is used to line moulds to give a durable, non contaminating release surface. It is also used to cover patterns, prior to the lay up of composite moulds
- Supplied with either a pressure sensitive silicone or acrylic adhesive backing
- Imparts a smooth surface finish on the cured laminate
- Self adhesive PTFE coated glass fabrics can only be applied in one piece to flat or single curvature tooling, however the material can be effectively butt jointed on complex tooling

	FF03AP	FF05AP	FF06AP	FF10AP
Max Temp Silicone (°C)	230	230	230	230
Max Temp Acrylic (°C)	180	180	180	180
Thickness (mm)	0.077	0.125	0.14	0.250
Adhesive Thickness (mm)	0.037	0.037	0.037	0.037
Weight of Material (g/m ²)	145	250	290	250

AVAILABILITY & PACKAGING

- Standard widths 1.00m also available in 1.52m wide
Slit tapes available
- Standard roll length 30m
Part rolls available

STORAGE & HANDLING

- No special requirements

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.