

FF/03/05/10PM PTFE Coated Glass Release Fabric

- FF03PM, FF05PM & FF10PM release fabric are medium porosity PTFE coated glass fabrics which have been used very successfully in the composite bonding industry for many years
- Ideal for use on flat or single curvature mouldings and its PTFE release coating ensures very easy release from the laminate without fear of contamination
- During coating of the glass fabric with PTFE, the porosity can be carefully controlled to give the desired resin flow through the fabric

PHYSICAL PROPERTIES

	FF03PM	FF05PM	FF10PM
Max Cure Temperature (°C)	320	320	320
Release Coating	PTFE	PTFE	PTFE
Fabric Weight (nominal)	63g/m ²	130g/m ²	230g/m ²
Fabric Thickness (nominal)	0.075mm	0.125mm	0.25mm
Porosity M/s	8	9	10

AVAILABILITY & PACKAGING

- Roll sizes
100m x 1.00m wide
100m x 1.52m wide
100m x 2.00m wide

STORAGE & HANDLING

- No special storage conditions required

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.

revision: May 2002