

FF05/O6AAP Self Adhesive PTFE Coated Glass Fabric Tool Release Sheet

- High gloss PTFE coated glass fabric tool release sheet is used to line moulds to give a durable, non contaminating release surface
- It has also been used successfully to cover patterns prior to the lay up of composite moulds
- Supplied with either a pressure sensitive silicone or acrylic adhesive backing
- Will impart a very smooth surface finish on the cured laminate
- Self adhesive PTFE coated glass fabrics can only be applied in one piece, to flat or single curvature tooling, however the material can be effectively butt jointed on complex tooling

	FF05AAP	FF06AAP
Max Temp Acrylic (°C)	180	180
Max Temp Silicone (°C)	230	230
Thickness (mm)	0.125	0.155
Adhesive Thickness (mm)	0.037	0.037
Weight of Material (g/m ²)	250	330

AVAILABILITY & PACKAGING

- Standard widths 1.00m and 1.52m wide
Slit tapes available
- Standard roll length 30m
Part rolls available

STORAGE & HANDLING

- No special requirements

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.