

Latex natural Rubber B Grade

- A high modulus material with good stretch and recovery. It is especially suitable for use as a vacuum blanket and release membranes where the temperature does not exceed 100°C

PHYSICAL PROPERTIES

• Maximum temperature use	100°C
• Colour	Natural
• Tensile strength	25 Mpa
• Elongation at break	800%
• Durometer hardness (Shore A)	40

SPECIFICATION

• Thickness range (nominal)	0.5mm - 3mm
• Widths available	up to 4.0 mtr

STORAGE & HANDLING

• Temperature	Store below 26°C and away from heaters
• Humidity	Avoid damp storage conditions
• Light	Protect from prolonged exposure to light, in particular bright sunlight and strong u/v light which will degrade sheeting
• Metals	Avoid contact with copper and copper containing alloys which may stain the sheeting
• Oils and solvents	Avoid contact with oils, solvents and greases which will destroy natural rubber

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.