

A2000 Release Film

- A2000 is an inexpensive release film, mainly used during the processing of flat or simple curvature components
- Exhibits excellent release characteristics from all commonly used resin systems
- Available coloured red for ease of identification on the cured laminate

PHYSICAL PROPERTIES

- | | |
|---------------------------|------------------------|
| • Maximum Use Temperature | Up to 155°C |
| • Perforations | P3, P6 and P31 |
| • Density | 0.955g/cm ³ |
| • Elongation at break | >400% |
| • Colour | Red |

AVAILABILITY & PACKAGING

- | | |
|-------------|--|
| • Thickness | 0.030mm and 0.050mm |
| • Yield | 0.030mm:- 37 m ² /Kg
0.050mm:- 24.6 m ² /Kg |
| • Roll size | 400m x 1.50m wide
(0.030 and 0.050mm) |

STORAGE & HANDLING

- Store in original packaging
- No handling problems experienced

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.