

# Rap Hold I

- Rap hold I is a general purpose, double backed tape, designed for use at temperatures up to 205°C
- It is a 0.001 polyester film, coated on both sides with a solvent resistant acrylic adhesive
- Performs excellent in resin dam hold down, inter bagging seal or any place where a two-sided tape is needed

## PHYSICAL PROPERTIES

• Maximum Use Temperature	205°C
• Film Substrate	Polyester
• Colour	Clear
• Adhesive	Acrylic
• Total Thickness	0.10mm
• Tensile	4.46Kg/cm width
• Elongation %	100
• Adhesion	390g/cm width

## AVAILABILITY & PACKAGING

- |          |                          |
|----------|--------------------------|
| • Widths | 6.3mm, 12.7mm and 25.4mm |
| • Length | 33m                      |

## STORAGE & HANDLING

- No special requirements

## Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: [sales@aerovac.com](mailto:sales@aerovac.com) website: [www.aerovac.com](http://www.aerovac.com)

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.