

SKAPO3/05/10 Skived PTFE Tool Release Sheet

- Smooth, un-reinforced, skived PTFE sheet
- Pressure sensitive adhesive applied to one side
- Silicone and acrylic adhesive available
- Most commonly used skived film in tool release applications, as it is quite flexible and easy to apply to the tool surface

	SKAP03	SKAP05	SKAP10
Max Temp Silicone (°C)	230	230	230
Max Temp Acrylic (°C)	180	180	180
Total Thickness (mm)	0.085	0.165	0.318
Adhesive Thickness (mm)	0.034	0.034	0.034
Elongation	320%	320%	350%
Tensile Strength (MPa)	25	30	35
Adhesion (N/cm)	3	5.8	5.5

AVAILABILITY & PACKAGING

- Standard width 1.00m
- Standard roll length 30m
Part rolls available
- Thickness Various available

STORAGE & HANDLING

- No special requirements

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.

revision: May 2002