

SM5130

Vacuum Bag Sealant Tape

- Excellent versatile tape for autoclave bonding, composite fabrication and vacuum processing at cure temperatures of up to 204°C
- Achieves rapid positive vacuum sealing with all tool surfaces and bagging materials and allows easy fabrication of pleats, pressure intensifiers and resin dams
- Strips cleanly and quickly from the mould surface, on cooling below 66°C

PHYSICAL PROPERTIES

- Maximum Use Temperature 204°C continuous
- Colour Grey
- Solids 100%
- Flammability Will not support combustion

AVAILABILITY & PACKAGING

- Roll size 9.14m x 12mm x 3mm
- Standard box contents 32 rolls

STORAGE & HANDLING

- SM5130 is non toxic, non irritant, and non injurious to skin
- Material should be used within 6 months of date of manufacture
- Material must be stored flat
- Cartons should not be stacked more than 5 high

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.