

# SM5160

## Vacuum Bag Sealant Tape

- A high temperature tape for use in autoclave bonding of thermoplastics, at temperatures of up to 399°C
- The consistency of the tape enables rapid vacuum sealing with high temperature bagging films, e.g. polyimide

### PHYSICAL PROPERTIES

- Maximum Use Temperature 399°C
- Colour Dark Brown
- Solids 100%
- Flammability Will not support combustion

### AVAILABILITY & PACKAGING

- Roll size 9.14m x 18mm x 3mm
- Standard box contents 24 rolls

### STORAGE & HANDLING

- SM5160 is non toxic, non irritant, and non injurious to skin
- Material should be used within 9 months of date of manufacture
- Material must be stored flat
- Cartons must not be stacked more than 5 high
- For optimum performance SM5160 should be kept refrigerated when not in use
- If SM5160 is stored below room temperature it should be allowed to return to room temperature before use

### Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: [sales@aerovac.com](mailto:sales@aerovac.com) website: [www.aerovac.com](http://www.aerovac.com)

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.

revision: 07/04/06