

SM9151

Vacuum Bag Sealant Tape

- An industry standard in autoclave bonding, composite fabrication and vacuum processing for cure temperatures up to 204°C
- Achieves rapid positive vacuum sealing with most available tool surfaces and bagging materials allowing easy fabrication of pleats, pressure pads and resin dams
- Strips cleanly and quickly from the mould surface on cooling below 66°C
- Excellent adhesion to all commonly used bagging films and tool surfaces, as well as a superb 'snap back' property

PHYSICAL PROPERTIES

- | | |
|---------------------------|-----------------------------|
| • Maximum Use Temperature | 204°C |
| • Colour | Pink |
| • Solids | 100% |
| • Flammability | Will not support combustion |

AVAILABILITY & PACKAGING

- Standard rolls, 9.14 metres long x 12mm x 3mm are packed in cardboard cartons containing 32 rolls

STORAGE & HANDLING

- SM9151 is non toxic, non irritant, non injurious to skin
- Material should be used within 12 months of date of manufacture
- Material must be stored flat
- Cartons must not be stacked more than 5 high

Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: sales@aerovac.com website: www.aerovac.com

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability of the product for this particular purpose and shall assume all risk and liability in connection herewith.

revision: N/A new