

# VAC PAK® UHT-750 Ultra High Temperature Bagging Film

- VAC PAK® UHT-750 is a high performance bagging film which will withstand continuous 426°C cure cycles
- It is flame resistant, does not melt, and resists effects of organic solvents
- VAC PAK® UHT-750 is transparent, permitting visibility of the lay up under the bag
- Ideally suited for release applications when treated with release agent

## PHYSICAL PROPERTIES

- Maximum Use Temperature 426°C
- Colour Transparent amber
- Elongation (maximum) > 90%
- Tensile Strength > 34,000 psi
- Shrinkage 1.2% (1 hour @ 426°C)
- Flammability Self extinguishing

## AVAILABILITY & PACKAGING

- Thickness 0.025mm, 0.050mm, 0.076mm
- Roll Weight 11.34Kg
- Yield 0.025mm - m<sup>2</sup>/Kg  
0.050mm - m<sup>2</sup>/Kg  
0.076mm - m<sup>2</sup>/Kg

## STORAGE & HANDLING

- No special requirements

## Aerovac Systems Ltd.

Tel: 01274 550500 Fax: 01274 550501 e-mail: [sales@aerovac.com](mailto:sales@aerovac.com) website: [www.aerovac.com](http://www.aerovac.com)

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability for this particular purpose and shall assume all risk and liability in connection herewith.